## **AMENDMENTS TO THE CLAIMS**

1. (Currently Amended) A method of approximating a motion vector for an image block for concealment of a lost or damaged motion vector, comprising the steps of:

deriving a first set of vectors from motion vectors of neighbouring blocks in the same frame and the corresponding block and its neighbouring blocks in one or more preceding and/or subsequent frames;

deriving a set of candidate vectors from one or more of motion vectors of neighbouring blocks in the same frame and the corresponding block and its neighbouring blocks in one or more preceding and/or subsequent frames;

deriving an estimated motion vector from the first set of vectors;

comparing the candidate vectors with the estimated motion vector; and

selecting one of the candidate vectors on the basis of similarity to said estimated vector;

and

utilizing the selected vector to conceal a lost or damaged motion vector.

- 2. (Canceled)
- 3. (Previously Presented) A method as claimed in claim 1, wherein the first set of vectors and the set of candidate vectors are the same.
  - 4. (Canceled)

Application No. 10/628,385 Amendment dated June 3, 2009

After Final Office Action of March 3, 2009

5. (Currently Amended) A method as claimed in claim 1, wherein the similarity

Docket No.: 1906-0119P

to the estimated vector is defined in terms of distance, size, or direction.

6. (Currently Amended) A method as claimed in claim 1 or claim 5, wherein the

vector that is closest or second closest to the estimated vector is selected.

7. (Previously Presented) A method as claimed in claim 1, wherein the estimated motion

vector is the mean of two or more or all of the elements of said first set.

8. (Currently amended) A method as claimed in claim 7 claim 7, wherein the mean is a

weighted mean.

9. (Currently Amended) A method as claimed in claim-8 claim 8, wherein motion

vectors of neighbouring blocks are weighted according to their position in relation to said image

block or their similarity to the motion vector of the block corresponding to said image block in

the preceding or subsequent frame.

10. (Previously Presented) A method as claimed in claim 1, wherein the selection takes

into account motion boundaries.

11-14. (Canceled)

3 MKM/PLC/

15. (Previously Presented) A tangible computer-readable medium storing instructions

that, when executed, cause a processor to perform a method as claimed in claim 1.

16-17. (Canceled)

18. (Previously Presented) A decoder comprising:

data decoding means for decoding received data according a coding technique;

error detecting means for detecting errors in the decoded data; and

a motion vector estimator configured to perform the method of claim 1 or claim 21.

19. (Previously Presented) A receiver for a communication system or a system for

retrieving stored data comprising:

a transceiver for transmitting and receiving data; and

a decoder as claimed in claim 18.

20. (Original) A receiver as claimed in claim 19 which is a mobile videophone.

21. (Currently Amended) A method of approximating a motion vector for an image

block for concealment of a lost or damaged motion vector, comprising the steps of:

deriving a first set of vectors from motion vectors of neighbouring blocks in the same

frame;

4 MKM/PLC/

After Final Office Action of March 3, 2009

deriving a set of candidate vectors from motion vectors of the corresponding block and its

neighbouring blocks in one or more preceding or subsequent frames;

determining an overall vector correlation between the vectors of the first set and the

vectors of the candidate set; and

approximating the motion vector from one or more of the motion vectors from the first

set or candidate set on the basis of the overall vector correlation; and

utilizing the approximated motion vector to conceal a lost or damaged motion vector.

22. (Previously Presented) A method as claimed in claim 21 wherein if the vector

correlation indicates a high correlation between the first set of vectors and the neighbouring

motion vectors in the preceding or subsequent frame of the candidate set then the motion vector

of corresponding block in the preceding or subsequent frame is selected as the approximated

motion vector.

23. (Previously Presented) A method as claimed in claim 21 or claim 22 wherein if the

vector correlation indicates a low correlation between the first set of vectors and the

neighbouring motion vectors in the preceding or subsequent frame of the candidate set then the

motion vector is approximated using motion vectors from the first set of vectors.

5 MKM/PLC/